

# PURE 70/70 MANUAL



PURE Manual (without ventilation) - Ecological combustion (obligation to connect 2 hot air hoses) - Sealed device

Steel door (PU70M-A-SV)

New look door (PU70M-NL-SV)

PURE Manual (with ventilation) - Forced convection - Sealed device

Steel door (PU70M-A-AV)

New look door (PU70M-NL-AV)

Kw	efficiency %	CO (mg/Nm <sup>3</sup> )	COG (mg/Nm <sup>3</sup> )	Dust (mg/Nm <sup>3</sup> )	NOX (mg/Nm <sup>3</sup> )	el_max (kw)	el_min (kw)	el_sb (kw)
10	78	1125	96	15	90	0,052	0,037	0,001

Options → External dimensions (mm) : 700 x 700 x 470

Flat frame PURE 70 - 3 sided - 40mm → 772 x 738,5

Flat frame PURE 70 - 4 sided - 40mm → 772 x 772

Frame PURE 70 - drawn steel - 4 sided - 10 mm - depth 20mm → 710 x 710

Frame PURE 70 - drawn steel - 4 sided - 10 mm - depth 55mm → 710 x 710

Speed controller with airstat (with ventilation)

Speed controller with thermostat ambient temperature (with ventilation)

Hot air tubes kit 125 Ø+ Air stop kit

Supplement hot air tubes kit 125 Ø+ Air stop kit (with ventilation)

Reserve door fitting

Black painted vermic. interior

## Included

Manual combustion air regulation - external air intake Ø 100 mm - baffle vermiculite - stop embers 45° angled stainless steel nozzle for smoke outlet Ø 150 mm - colour antracite - 2 warm air tubes Ø 125 mm - WITHOUT FINISHING FRAME (following your choice)  
Real view of fire (mm) - 532 x 514



