

PURE XL16/9 MANUAL (PUXL16-9-v2)



PURE XL Manual (without ventilation) - Ecological combustion (obligation to connect 2 hot air hoses) - Sealed device

Steel door (PUXL-16-9M-A-SV)

New look door (PUXL-16-9M-NL-SV)

PURE XL Manual (with ventilation) - Forced convection - Sealed device

Steel door (PUXL-16-9M-A-AV)

New look door (PUXL-16-9M-NL-AV)

Kw	efficiency %	CO (mg/Nm ³)	COG (mg/Nm ³)	Dust (mg/Nm ³)	NOX (mg/Nm ³)	el_max (kw)	el_min (kw)	el_sb (kw)
13	81	1213	71	15	115	0,052	0,037	0,001

Options

→ External dimensions (mm) : 1000 x 600 x 475

Flat frame PURE XL 16-9 - 3 sided - 40mm

→ 1072 x 637,5

Flat frame PURE XL 16-9 - 4 sided - 40mm

→ 1072 x 671

Frame PURE XL 16-9 - drawn steel - 4 sided - 10 mm - depth 20mm

→ 1010 x 610

Frame PURE XL 16-9 - drawn steel - 4 sided - 10 mm - depth 55mm

→ 1010 x 610

Speed controller with astat (with ventilation)

Speed controller with thermostat ambient temperature (with ventilation)

Hot air tubes kit 125 Ø+ Air stop kit

Supplement hot air tubes kit 125 Ø+ Air stop kit (with ventilation)

Reserve door fitting

Black painted vermic. interior

Included

Manual combustion air regulation - external air intake Ø 100 mm - double baffles (vermiculite + inox) - stop embers - interior vermiculite - 45° angled stainless steel P Ø 200 mm nozzle for smoke outlet - colour antracite - 2 warm air tubes Ø 125 mm - WITHOUT FINISHING FRAME (following your choice)

Real view of fire (mm) - 846 x 404



